




blum.com


















# **Easy assembly**

The LEGRABOX front fixing bracket enables fast and above all safe assembly and removal. You just need to place the front in its holding position and it will easily clip into place. The front can even be easily assembled on a pull-out that has already been installed. The 3-dimensional front adjustment positioned on the interior of the drawer side, provides a constant front positioning when closed and a highly constant gap design, irrespective of the front dimension.

**ablum** 





### **BLUMOTION**

BLUMOTION soft-close technology is integrated into the cabinet profile and adapts itself to the size, weight and speed of the closing furniture.



#### **SERVO-DRIVE**

With SERVO-DRIVE electrical motion support, a light touch on the handle-less front or a gentle pull on the handle opens furniture.


SERVO-DRIVE is compatible with BLUMOTION soft-close, enhancing comfort and freedom of motion.



# **TIP-ON BLUMOTION**

Offering functional opening and closing support for handle-less furniture is TIP-ON BLUMOTION, our 100% mechanical opening and soft closing support system. This technology combines two competing forces and makes for a completely harmonious experience when operating drawers and pull-outs.





# Slimline design

At 12.8mm and straight on the inside and outside, the impressively slim side panels make complete use of the interior.



# **New colour concept**


LEGRABOX features a completely new colour concept made from either anti-fingerprint stainless steel or steel with a matt coating giving it a special feel.



# **Individual branding**

Branding is an integral part of the LEGRABOX pure design and can be printed with your company name or logo.









LEGRABOX pure in Anti-fingerprint Stainless Steel in a cutlery and odds and ends drawer application in the kitchen. This features a M height drawer and inner drawer.




 $\label{lem:lemma$ 




LEGRABOX pure C height pull-out in Terra Black Matt in a living room furniture application.






blum







For a harmonious overall concept LEGRABOX free is suitable for use in furniture throughout the home including wardrobe or living room furniture.





# **Universal programme**

The LEGRABOX pure programme is versatile and suited to any living area. The box system allows for a variety of applications that can be implemented in different heights and colours.





# **LEGRABOX** pure – drawer and inner drawer



#### **Drawer**

Drawer side height M (90.5 mm)

#### **Nominal lengths**

270 mm

350 mm

400 mm

450 mm

500 mm

550 mm

600 mm



#### Inner drawer

Drawer side height M (90.5 mm)

Front piece for cutting to size.



#### **Drawer**

Drawer side height K (128.5 mm)

### **Nominal lengths**

350 mm

400 mm

450 mm

500 mm

550 mm

# **LEGRABOX** pure and **LEGRABOX** free – high fronted pull-out and inner pull-out





#### High fronted pull-out

Drawer side height C (177 mm)

#### Nominal lengths LEGRABOX pure

350 mm 500 mm 400 mm 550 mm 450 mm 600 mm

#### Nominal lengths LEGRABOX free

450 mm 550 mm



# Inner pull-out

Drawer side height C (177 mm) Front piece\* with high design element





#### Inner pull-out

Drawer side height C (177 mm) Front piece\* with low design element



#### Inner pull-out

Drawer side height C (177 mm) Front piece\* with gallery

\* Front piece for cutting to size



#### High fronted pull-out

Drawer side height F (241 mm)

#### **Nominal lengths**

450 mm 500 mm 550 mm

600 mm

### **Motion Technologies**

The LEGRABOX product range includes Blum's integrated, adaptive dampening system BLUMOTION which ensures it closes silently and effortlessly.

LEGRABOX is compatible with SERVO-DRIVE, Blum's electrical motion support system.

LEGRABOX is available in a version compatible with TIP-ON BLUMOTION mechanical opening and soft closing support system.

BLUMOTION by Blum

SERVO-DRIVE

by B**l**um

TIP-ON BLUMOTION by Blum







#### **Base router**

Ensures easy and precise rebating of the LEGRABOX drawer/pull-out base.



# **Drilling template for LEGRABOX**

For precise pre-drilling on the base and back.



# **MINISTICK** (new)

Facilitates easy and precise drilling for LEGRABOX when using Blum's MINIPRESS P (retrofit option).



# **BOXFIX E-L**

Provides simple yet precise manual assembly of LEGRABOX drawers and pull-outs.




# **Universal drilling template**

The multifunctional assembly device for pre-drilling of fixing positions for cabinet profiles.



# **Universal drilling template**

The multifunctional assembly device for pre-drilling on the drawer front.






# **Uniform design**

The elegance of LEGRABOX continues throughout kitchen and furniture interiors with AMBIA-LINE inner dividing frames. The narrow, straightforward design of the frames complement LEGRABOX in both colour and style for a harmonious look in all living areas.

**Ablum** 

# Perfect organisation

AMBIA-LINE creates order within LEGRABOX with simple elegance.



# Individual adjustment

The flexible cross dividers can be easily adjusted to fit the size of the goods being stored.



# **Easy utilisation**

The frames are easy to insert and can be positioned as desired. Steel frames for the high fronted pull-out are held securely by a magnet.



# **Complete programme**

The AMBIA-LINE programme is clear and diverse. AMBIA-LINE frames are compact, versatile and easily positioned in any configuration to suit individual needs, without a need for tools. In addition to the range of narrow frames, a customised cross gallery rail is also available to accommodate specific storage solutions for plastic containers, lids, pots and pans.

Ablum

### Classic steel design

The powder coated steel frames are available in three colours, so drawers and interiors can be made to match.



Orion Grey Matt



Terra Black Matt



Silk White Matt



# AMBIA-LINE for drawers (drawer side heights M and K)



Cutlery insert Width 300 mm




Drawer frame for short nominal lengths of 300 mm or more. Width 242 mm, Length 270 mm



Narrow drawer frame Width 100 mm



Wide drawer frame Width 200 mm



AMBIA-LINE knife holder

Up to nine knives can be stored safely in the knife holder. Suitable for drawer frames with a width of 200 mm.



**AMBIA-LINE** foil dispenser

Plastic film and aluminium foil can be pulled out and cleanly cut with the film & foil dispenser. Suitable for drawer frames with a width of 200 mm.

# AMBIA-LINE for high fronted pull-outs (drawer side heights C and F)



High fronted pull-out frame for nominal lengths of 270 mm or more. Width 242 mm, Length 270 mm



High fronted pull-out frame for nominal lengths of 400 mm or more. Width 218 mm, Length 370 mm



Cross gallery for cutting to size and lateral divider.



Bottle set for width 100 mm or width 200 mm.



Blum plate holder

Up to 12 plates can be held securely and conveniently transported using the plate holder in the pull-out.



### AMBIA-LINE spice holder

All spice containers are stored securely and with a clear overview in the spice holder. Suitable for high fronted pull-out frames with a width of 218 mm (for nominal lengths of 400 mm or more).





# **Practical kitchens**

Well designed products like LEGRABOX and AMBIA-LINE bring high levels of functionality to every kitchen. LEGRABOX impresses with its ability to withstand intense daily use for the lifetime of the furniture.

AMBIA-LINE is a simple way of creating and enabling fluid work processes.

**Ablum** 



# Blum's ideas for practical kitchens

A kitchen has to be fit for everyday use. That's why Blum has been researching the requirements of kitchen users for years. In this way, new ideas for making modern kitchens even more practical are constantly being generated as part of DYNAMIC SPACE. More information can be found at blum.com

#### Simple workflows

LEGRABOX drawers and pull-outs are fully extendable providing complete overview and easy access right into the back corner.

AMBIA-LINE dividers guarantee order and organisation of all stored items such as cooking utensils, bottles and provisions.



# **Space optimisation**


Maximise the use of available space by planning kitchens with wide, high and deep pull-outs. The straight and slim profile of LEGRABOX allows for complete use of the interior. With AMBIA-LINE your customers can organise the space to suit the items being stored.



### **Top quality motion**

With low opening forces, incredibly smooth running action and integrated BLUMOTION soft-close, LEGRABOX increases comfort in the kitchen. Combine with SERVO-DRIVE electrical motion support for superior quality of motion and enhanced user convenience.





### **Sink Cabinet**

Blum's Sink Cabinet makes optimal use of available space in the cabinet under the sink. Additional usable space is gained via the u-shaped cut out with the Sink Drawer. Also included in the Sink Cabinet is the waste bin pull-out.



#### **SPACE TOWER**

Blum's SPACE TOWER is the optimal pantry solution. Utilising fully extendable individual pull-outs, contents are easily accessible from all three sides and into the farthest corner. This solution can also be adapted to suit bedroom wardrobe and living room cabinets.





### **Narrow Cabinets**

Blum's Narrow Cabinets solution makes use of otherwise wasted yet valuable storage space in kitchens. This is especially practical when positioned close to the preparation bench or stove for the bottle and spice storage, carrying up to 20 kgs.











AMBIA-LINE frame in Silk White Matt.



LEGRABOX pure, pull-out side height C in Terra Black Matt, AMBIA-LINE frame in Terra Black Matt.



LEGRABOX free, pull-out height C in Silk White Matt with stone design element, AMBIA-LINE frames in Silk white.





## **Services for the Manufacturer**

Blum would like to make the ordering, assembly and marketing of its products as easy as possible for our customers and partners. A variety of useful online applications as well as special planning and ordering software are available to support your daily activities.

**Ablum** 



#### Product Configurator


The Product Configurator assists with the selection and ordering of the correct fittings. Along with parts lists for your desired fitting solution, you also get marketing information, manufacturing and assembly documentation as well as 2D/3D CAD data.

www.blum.com/product configurator




#### **DYNALOG**

Using Blum's DYNALOG planning software, the cabinet planning for Blum fittings is complete and precise. The program can be operated intuitively, automatic collision checks ensure that designs are feasible and do away with trial applications.



#### **DYNAPLAN** interfaces

Complete plans can be exported and imported to or from your CAD or CAM system at the touch of a button via interfaces in DYNAPLAN. In this way, DYNAPLAN supports your main program with both every-day solutions as well as special constructions.






Precision installation and adjustment have an impact on top quality motion. At Blum, we would like to make it as easy as possible for manufacturers, cabinet makers and installers to use Blum products in workshops and on-site.



#### **EASY ASSEMBLY App**

Blum's complimentary
EASY ASSEMBLY App
provides cabinetmakers
and installers with useful
instructions and videos
that support on-site
assembly, installation
and adjustment of
Blum fittings.



## Simple assembly instructions

Blum products come with easy step-by-step assembly instructions. Assembly and installation instructions can also be found in Blum's trade catalogue and can be downloaded from the Media Centre on Blum's website.




#### **Practical templates**

Blum's practical templates are a perfect combination of high precision and practical value. These templates can be used in workshops and are easily transported to support on-site assembly and installation.



# LEGRABOX pure LEGRABOX free

#### **Material and colour**



Terra Black Matt Orion Grey Matt Silk White Matt Anti-Fingerprint Stainless Steel

>	Material and cold	our			
4		SW-M	OG-M	TS-M	INGL
	***	Silk White Matt	Orion Grey Matt	Terra Black Matt	Stainless steel With an anti-fingerprint coating
SW-M		_			
Silk Wh	ite Matt				
OG-M	_		_		
Orion G	irey Matt		_		
TS-M				_	
Terra Bl	ack Matt			_	
NI					
Nickel					_
Nickel N	Matt				-


## **Drawer – height M**

**LEGRABOX** pure

*ablum* 

#### **Product**





#### **Order specification**

1	Cabinet profiles left/right	Cabinet profiles left/right							
20	Nominal length	BLUMOT	ION*			TIP-ON E	BLUMOTION		
	270 mm	40 kg	750.2701B			40 kg	750.2701M		
	350 mm	40 kg	750.3501B			40 kg	750.3501M		
	400 mm	40 kg	750.4001B			40 kg	750.4001M		
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501M	70 kg	753.4501M
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001M	70 kg	753.5001 <b>M</b>
	550 mm			70 kg	753.5501B			70 kg	753.5501 <b>M</b>
	600 mm			70 kg	753.6001B			70 kg	753.6001 <b>M</b>

2	Drawer side set						
	Consisting of:						
	2a drawer side left/right						
	2b cover caps (external)						
	2c cover caps (internal)						
		Colour variants					
		SW-M	OG-M	TS-M	INGL		
	Nominal length		Steel		Stainless steel**		
	270 mm		770M2702S				
	350 mm		770M3502S				
	400 mm		770M4002S		770M4002I		
	450 mm		770M4502S		770M4502I		
	500 mm		770M5002S		770M5002I		
	550 mm		770M5502S		770M5502I		
	600 mm		770M6002S				

<sup>\*</sup> Suitable for SERVO-DRIVE

<sup>\*\*</sup> With anti-fingerprint coating


## Drawer - height M








Accessori	es
	Fixing screws for front fixing brackets
	Ø 3.5 x 15 mm
₹	Ø 3.5 x 17 mm
	Fixing screws for wooden back fixings and drawer sides with drawer base
	Ø 4 x 15 mm
₩	In order to achieve optimal assembly, we recommend that you use flat headed screws.






# Inner drawer - height M front piece closed

**LEGRABOX** pure

*iblum* 

#### **Product**





1	Cabinet profiles left/right								
20.	Nominal length	BLUMOT	ION*			TIP-ON E	LUMOTION		
	270 mm	40 kg	750.2701B			40 kg	750.2701M		
	350 mm	40 kg	750.3501B			40 kg	750.3501 <b>M</b>		
	400 mm	40 kg	750.4001B			40 kg	750.4001 <b>M</b>		
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501 <b>M</b>	70 kg	753.4501 <b>M</b>
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001 <b>M</b>	70 kg	753.5001 <b>M</b>
	550 mm			70 kg	753.5501B			70 kg	753.5501M
	600 mm			70 kg	753.6001B			70 kg	753.6001M

2	Drawer side set				
	Consisting of:				
	2a drawer side left/right				
46	2b cover caps (external)				
	2c cover caps (internal)				
		Colour variants			
		SW-M	OG-M	TS-M	INGL
	Nominal length		Steel		Stainless steel**
	270 mm		770M2702S		
	350 mm		770M3502S		
	400 mm		770M4002S		770M4002I
	450 mm		770M4502S		770M4502I
	500 mm		770M5002S		770M5002I
	550 mm		770M5502S		770M5502I
	600 mm		770M6002S		

<sup>\*</sup> Suitable for SERVO-DRIVE

<sup>\*\*</sup> With anti-fingerprint coating

# Inner drawer – height M front piece closed

### Ablum



4	Fro	nt piece set				
F37 100	Cor	sisting of:				
J 3	4a	Front fixing left / right				
	4b	Outer cover caps left/right				
• • • • • • • • • • • • • • • • • • • •	4c	Locking piece				
	4d	Screws				
			Colour variants			
			SW-M	OG-M	TS-M	INGL
				Steel		Stainless steel**
				ZI7.0MS0		ZI7.0MI0

5	Late	ch set (optional)					
	Con	sisting of:					
	5a	Latch					
	5b	b Trigger housing (RAL 7037 dust grey)					
			Colour variants				
			SW-M	OG-M	TS-M	TS-M¹)	
		Plastic					
					Z17.0M	107	

6	Wooden back fixing brackets left/rig	looden back fixing brackets left/right					
		olour variants					
		SW-M OG-M TS-M	Nickel				
		Steel					
	Height M	ZB7M00	00S				

#### Accessories

Fixing screws for wooden back fixings and drawer sides with drawer base



Ø 4 x 15 mm

In order to achieve optimal assembly, we recommend that you use flat headed screws.



#### **SERVO-DRIVE** applications

For additional components required for SERVO-DRIVE applications refer to page 68



#### **TIP-ON BLUMOTION**

For additional components required for TIP-ON BLUMOTION applications refer to page 69

For Anti-fingerprint Stainless Steel applications, the latch set in Terra Black Matt is recommended.


<sup>\*\*</sup> With anti-fingerprint coating

## Drawer - height K



#### **Product**





1	Cabinet profiles left/right								
100 .	Nominal length	BLUMOT	ION*			TIP-ON E	BLUMOTION		
	350 mm	40 kg	750.3501B			40 kg	750.3501M		
	400 mm	40 kg	750.4001B			40 kg	750.4001M		
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501M	70 kg	753.4501M
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001M	70 kg	753.5001M
	550 mm			70 kg	753.5501B			70 kg	753.5501 <b>M</b>

2	Drawer side set			
1.	Consisting of:			
	2a drawer side left/right			
	2b cover caps (internal)			
	2c cover caps (external)			
		Colour variants		
		SW-M	OG-M	TS-M
	Nominal length		Steel	
	350 mm		770K3502S	
	400 mm		770K4002S	
	450 mm		770K4502S	
	500 mm		770K5002S	
	550 mm		770K5502S	

3	Front fixing bracket		
M	EXPANDO	2 x	ZF7K70E2
<b>3</b>	Screw-on	2 x	ZF7K7002

<sup>\*</sup> Suitable for SERVO-DRIVE


## **Drawer - height K**





Accessori	es
	Fixing screws for front fixing brackets screw-on application
¥	Ø 3.5 x 15 mm
₹	Ø 3.5 x 17 mm
	Fixing screws for wooden back fixings and drawer sides with drawer base
	Ø 4 x 15 mm
₹	In order to achieve optimal assembly, we recommend that you use flat headed screws.

# SERVO-DRIVE applications For additional components required for SERVO-DRIVE applications refer to page 68




## High fronted pull-out – height C

LEGRABOX pure

*iblum* 

#### **Product**





1	Cabinet profiles left/right									
M a	Nominal length	BLUMOT	ION*			TIP-ON BLUMOTION				
	350 mm	40 kg	750.3501B			40 kg	750.3501 <b>M</b>			
	400 mm	40 kg	750.4001B			40 kg	750.4001 <b>M</b>			
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501 <b>M</b>	70 kg	753.4501M	
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001 <b>M</b>	70 kg	753.5001M	
	550 mm			70 kg	753.5501B			70 kg	753.5501M	
	600 mm			70 kg	753.6001B			70 kg	753.6001M	


2	Drawer side set				
1.	Consisting of:				
	2a drawer side left/right				
	2b cover caps (external)				
	2c cover caps (internal)				
		Colour variants			
		SW-M	OG-M	TS-M	INGL
	Nominal length		Steel		Stainless steel**
	350 mm		770C3502S		
	400 mm		770C4002S		770C4002I
	450 mm		770C4502S		770C4502I
	500 mm		770C5002S		770C5002I
	550 mm		770C5502S		770C5502I
	600 mm		770C6002S		

<sup>\*</sup> Suitable for SERVO-DRIVE

<sup>\*\*</sup> With anti-fingerprint coating

## High fronted pull-out – height C


## Ablum





Accessori	es
	Fixing screws for front fixing brackets screw-on application
) I	Ø 3.5 x 15 mm
₹	Ø 3.5 x 17 mm
	Fixing screws for wooden back fixings and drawer sides with drawer base
	Ø 4 x 15 mm
₩	In order to achieve optimal assembly, we recommend that you use flat headed screws.






# Inner pull-out – height C – front piece with a high or low design element

**LEGRABOX** pure

**Ablum** 

#### **Product**





1	Cabinet profiles left/right								
M o	Nominal length	BLUMOT	rion*			TIP-ON BLUMOTION			
	350 mm	40 kg	750.3501B			40 kg	750.3501 <b>M</b>		
	400 mm	40 kg	750.4001B			40 kg	750.4001 <b>M</b>		
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501 <b>M</b>	70 kg	753.4501M
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001 <b>M</b>	70 kg	753.5001M
	550 mm			70 kg	753.5501B			70 kg	753.5501M
	600 mm			70 kg	753.6001B			70 kg	753.6001M

2	Drawer side set				
1.	Consisting of:				
	2a drawer side left/right				
	2b cover caps (external)				
	2c cover caps (internal)				
		Colour variants			
		SW-M	OG-M	TS-M	INGL
	Nominal length		Steel		Stainless steel**
	350 mm		770C3502S		
	400 mm		770C4002S		770C4002I
	450 mm		770C4502S		770C4502I
	500 mm		770C5002S		770C5002I
	550 mm		770C5502S		770C5502I
	600 mm		770C6002S		

3	Front piece with groove								
	Colour variants								
		SW-M OG-M TS-M Nickel Matt							
3		Aluminium							
	For cutting to size	ZV7.1043MN1							
	Cutting LW - 126 mm	LW Inner cabinet width							

<sup>\*</sup> Suitable for SERVO-DRIVE

<sup>\*\*</sup> With anti-fingerprint coating

## **Ablum**

## Inner pull-out – height C – front piece with a high or low design element



5	Wooden back fixing brackets left/right								
		Colour variants							
		SW-M	OG-M	TS-M	Nickel				
		Steel							
	Height C			ZB7C000S					

6	High glass design element (for inner pull-out front)							
	Individually cut to size							
	Cabinet width	Side panel thickness 15 and 16 mm						
7	450 mm	1 x	ZE7W338G					
	600 mm	1 x	ZE7W488G					
	900 mm	1 x	ZE7W788G					
	1200 mm	1 x	ZE7W1088G					

6	Low glass design element (for inner pull-out front)							
	Individually cut to size							
	Cabinet width		Side panel thickness 15 and 16mm					
	450 mm	1 x	ZE7V338G					
	600 mm	1 x	ZE7V488G					
	900 mm	1 x	ZE7V788G					
	1200 mm	1 x	ZE7V1088G					

#### Accessories

Ø 4 x 15 mm

Fixing screws for wooden back fixings and drawer sides with drawer base

In order to achieve optimal assembly, we recommend that you use flat headed screws.



#### **SERVO-DRIVE** applications

For additional components required for SERVO-DRIVE applications refer to page 68



#### TIP-ON BLUMOTION

For additional components required for TIP-ON BLUMOTION applications refer to page 69

<sup>\*\*</sup> With anti-fingerprint coating


## Inner pull-out – height C – front piece with gallery





#### **Product**





1	Cabinet profiles left/right								
	Nominal length	BLUMOT	ION*			TIP-ON BLUMOTION			
	350 mm	40 kg	750.3501B			40 kg	750.3501 <b>M</b>		
	400 mm	40 kg	750.4001B			40 kg	750.4001 <b>M</b>		
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501M	70 kg	753.4501 <b>M</b>
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001 <b>M</b>	70 kg	753.5001 <b>M</b>
	550 mm			70 kg	753.5501B			70 kg	753.5501 <b>M</b>
	600 mm			70 kg	753.6001B			70 kg	753.6001M

2	Drawer side set				
	Consisting of:				
	2a drawer side left/right				
	2b cover caps (external)				
	2c cover caps (internal)				
		Colour variants			
		SW-M	OG-M	TS-M	INGL
	Nominal length		Steel		Stainless steel**
	350 mm		770C3502S		
	400 mm		770C4002S		770C4002I
	450 mm		770C4502S		770C4502I
	500 mm		770C5002S		770C5002I
	550 mm		770C5502S		770C5502I
	600 mm		770C6002S		

3	Front piece w	Front piece without groove										
Colour variants												
			SW-M	OG-M	TS-M	Nickel Matt						
					Aluminium							
	For cutting to	size			ZV7.1043C01							
	Cutting	LW - 126 mm	LW Inner cal	binet width								

<sup>\*</sup> Suitable for SERVO-DRIVE

<sup>\*\*</sup> With anti-fingerprint coating

### Inner pull-out - height C - front piece with gallery

### Ablum




5	Cross gallery											
			Colour variants									
			SW-M	OG-M	TS-M	Nickel Matt						
				Aluminium								
	For cutting to si	ze			ZR7.1080U							
	Cutting	LW - 90 mm	LW Inner cabine	et width								

6	Wooden back fixing brackets left/rig	ht					
A.		Colour variants					
		SW-M OG-M	TS-M	Nickel			
			Steel				
	Height C		ZB7C000S				
<u> </u>							

# Accessories Fixing screws for wooden back fixings and drawer sides with drawer base Ø 4 x 15 mm In order to achieve optimal assembly, we recommend that you use flat headed screws.





<sup>\*\*</sup> With anti-fingerprint coating


## High fronted pull-out – height C

**LEGRABOX** free

*iblum* 

#### **Product**





1	Cabinet profiles left/right										
11/2 0	Nominal length		TIP-ON BLUMOTION								
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501M	70 kg	753.4501 <b>M</b>		
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001M	70 kg	753.5001M		
	550 mm			70 kg	753.5501B			70 kg	753.5501M		

2	Drawer side set				
4	Consisting of:				
	2a drawer side left/right				
o to	2b cover caps (external)				
	2c BOXCOVER front				
	2d BOXCOVER back				
		Colour variants			
		SW-M	OG-M	TS-M	INGL
	Nominal length		Steel		Stainless steel**
	450 mm		780C4502S		780C4502I
	500 mm		780C5002S		780C5002I
	550 mm		780C5502S		780C5502I

3	Front fixing bracket	
OPa,	EXPANDO 4 x	ZF7M70E2
	Screws 4 x	ZF7M7002
QID.		


<sup>\*</sup> Suitable for SERVO-DRIVE

<sup>\*\*</sup> With anti-fingerprint coating

#### **LEGRABOX** free

### High fronted pull-out - height C







#### **SERVO-DRIVE** applications

For additional components required for SERVO-DRIVE applications refer to page 68



#### **TIP-ON BLUMOTION**

For additional components required for TIP-ON BLUMOTION applications refer to page 69


# Inner pull-out – height C – front piece with a high or low design element

**LEGRABOX** free

*ablum* 

#### **Product**





1	Cabinet profiles left/right									
De a	Nominal length	BLUMOT	ION*			TIP-ON E	BLUMOTION			
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501M	70 kg	753.4501M	
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001M	70 kg	753.5001M	
	550 mm			70 kg	753.5501B			70 kg	753.5501M	

2	Drawer side set				
4	Consisting of:				
	2a drawer side left/right				
o the a	2b cover caps (external)				
	2c BOXCOVER front				
	2d BOXCOVER back				
		Colour variants			
		SW-M	OG-M	TS-M	INGL
	Nominal length		Steel		Stainless steel**
	450 mm		780C4502S		780C4502I
	500 mm		780C5002S		780C5002I
	550 mm		780C5502S		780C5502I

3	Front piece with groove	
		SW-M OG-M TS-M Nickel Matt
		Aluminium
	For cutting to size	ZV7.1043MN1
	Cutting LW - 126 mm	LW Inner cabinet width

<sup>\*</sup> Suitable for SERVO-DRIVE

<sup>\*\*</sup> With anti-fingerprint coating

## **LEGRABOX** free

## *ablum*°

# Inner pull-out – height C – front piece with a high or low design element

4	Front piece set						
	Consisting of:						
	4a Front fixing left / right						
	4b Outer cover caps left/right						
I I I I	4c Interior cover cap left/right						
	4d Adapter piece for low design elen	nent left/right					
	4e Locking piece						
, (1)	4f Screws	Colour variants					
			00.14	T0.14	. Wor		
		SW-M	OG-M	TS-M	INGL		
			Steel		Stainless steel**  ZI7.2CI0		
			ZI7.2CS0		217.2010		
5	Wooden back fixing brackets left/rig	aht					
	Woodon back name brackets for a re-	,,,,					
		SW-M	OG-M	TS-M	Nickel		
		SVV-IVI	OG-W	Steel	Nickei		
	Height C			ZB7C000S			
	rioigiii o						
6	High glass design element (for inner	· pull-out front)					
	Individually cut to size			Side panel thickness			
	Cabinet width			15 and 16 mm			
	450 mm		1 x		ZE7W338G		
	600 mm		1 x		ZE7W488G		
	900 mm		1 x		ZE7W788G		
	1200 mm		1 x		ZE7W1088G		
6	Low glass design element (for inner	pull-out front)					
	Individually cut to size			Side panel thickness			
	Cabinet width			15 and 16 mm			
	450 mm		1 x		ZE7V338G		
	600 mm		1 x		ZE7V488G		
	900 mm		1 x		ZE7V788G		
	1200 mm		1 x		ZE7V1088G		
7	Glass design element (side)						
7	Glass design element (side) Nominal length						
7			1 x		ZE7S338G		
7	Nominal length		1 x 1 x		ZE7S338G ZE7S388G		

<sup>\*\*</sup> With anti-fingerprint coating

# Inner pull-out – height C – front piece with a high or low design element

**LEGRABOX** free

**Ablum** 

#### **Order specification**

Accessorie	es	
	Transportation lock for design element (side)	
ANT	For transporting pre-assembled design elements (side)	
	per pull-out x 2	780C0009
	Fixing screws for wooden back fixings and drawer sides with drawer base	
	Ø 4 x 15 mm	
₩	In order to achieve optimal assembly, we recommend that you use flat headed screws.	



#### SERVO-DRIVE applications

For additional components required for SERVO-DRIVE applications refer to page 68



#### TIP-ON BLUMOTION

For additional components required for TIP-ON BLUMOTION applications refer to page 69


### **LEGRABOX** free

## Inner pull-out - height C - front piece with gallery


## *ablum*

#### **Product**





#### **Space requirement**



#### **Order specification**

1	Cabinet profiles left/right										
All a	Nominal length	BLUMOT	ION*			TIP-ON B	LUMOTION				
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501M	70 kg	753.4501M		
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001 <b>M</b>	70 kg	753.5001M		
	550 mm			70 kg	753.5501B			70 kg	753.5501M		

2	Drawer side set						
4	Consisting of:						
	2a drawer side left/right						
	2b cover caps (external)	2b cover caps (external)					
Un Un	2c BOXCOVER front						
	2d BOXCOVER back						
		Colour variants					
		SW-M	OG-M	TS-M	INGL		
	Nominal length	Steel			Stainless steel**		
	450 mm	780C4502S			780C4502I		
	500 mm	780C5002S			780C5002I		
	550 mm		780C5502S		780C5502I		

3	Front piece without groove							
			Colour variants					
			SW-	-M	OG-M	TS-M	INGL	
	For cutting to size			Aluminium				
				ZV7.1043C01				
	Cutting	LW - 126 mm	LW Inr	ner cabine	t width			

<sup>\*</sup> Suitable for SERVO-DRIVE

<sup>\*\*</sup> With anti-fingerprint coating

### Inner pull-out - height C - front piece with gallery

**LEGRABOX** free

Ablum

#### **Order specification**



5	Cross gallery							
		Colour variants						
		SW-M	OG-M	TS-M	Nickel Matt			
		Aluminium						
	For cutting to size	ZR7.1080U						
	Cutting							
	LW - 90 mm							
	LW Inner cabinet width							

6		Wooden back fixing brackets left/right							
Sh.			Colour variants						
	BEI		SW-M	OG-M	TS-M	Nickel			
			Steel						
		Height C			ZB7C000S				
De 9									
	Ø								

7	Glass design element (side)					
	Nominal length					
	450 mm	1 x	ZE7S338G			
	500 mm	1 x	ZE7S388G			
	550 mm	1 x	ZE7S438G			

## Accessories Transportation lock for design element (side) For transporting pre-assembled design elements (side) 780C0009 2 x **SERVO-DRIVE** applications

applications refer to page 68

For additional components required for SERVO-DRIVE



Ø 4 x 15 mm

#### Fixing screws for wooden back fixings and drawer sides with drawer base

In order to achieve optimal assembly, we recommend that you use flat headed screws.

	TIP-ON BLUMOTION
9	For additional components required for TIP-ON BLUMOTION applications refer to page 69


<sup>\*</sup> With anti-fingerprint coating

## High fronted pull-out – height F

*ablum* 

#### **Product**





1	Cabinet profiles left/right								
M o	Nominal length	BLUMOTION*				TIP-ON BLUMOTION			
	450 mm	40 kg	750.4501B	70 kg	753.4501B	40 kg	750.4501 <b>M</b>	70 kg	753.4501 <b>M</b>
	500 mm	40 kg	750.5001B	70 kg	753.5001B	40 kg	750.5001M	70 kg	753.5001 <b>M</b>
	550 mm			70 kg	753.5501B			70 kg	753.5501 <b>M</b>
	600 mm			70 kg	753.6001B			70 kg	753.6001M

2	Drawer side set								
	Consisting of:								
	2a drawer side left/right	2a drawer side left/right							
	2b cover caps (external)								
700	2c cover caps (internal)								
		Colour variants							
		SW-M	OG-M	TS-M					
	Nominal length		Steel						
	450 mm		770F4502S						
	500 mm		770F5002S						
	550 mm		770F5502S						
	600 mm		770F6002S						


3	Front fixing bracket	
	EXPANDO 6 x	ZF7M70E2
<b>Ø</b>	Screw-on 6 x	ZF7M7002

<sup>\*</sup> Suitable for SERVO-DRIVE

## High fronted pull-out – height F


**LEGRABOX** pure





	Fixing screws for front fixing brackets
¥	Ø 3.5 x 15 mm
¥	Ø 3.5 x 17 mm
	Fixing screws for wooden back fixings and drawer sides with drawer base
	Ø 4 x 15 mm
V	In order to achieve optimal assembly, we recommend that you use flat headed screws.





## **SERVO-DRIVE** for LEGRABOX

*ablum* 

# Additional components required for SERVO-DRIVE applications

#### **Product**





#### **Order specification**

1	Blum distance bumper	
	Diameter	Part number
C/18	Ø 5 mm	993.0530
(2)	Front heights up to 300 mm x 2	
-	Front heights greater than 300 mm x 4	

2	Back profile								
_	Length	Material	Cable	Part number					
	670 mm	Aluminium	With	Z10T670AA					
	750 mm	Aluminium	With	Z10T750AA					
Л	1170 mm for cutting to size Internal cabinet height LH – 10 mm	Aluminium	Without	Z10T1170A					

3a	Bracket profile attachment top/bottom						
ONE.	Material	Colour	Part number				
	Nylon	Dust grey	Z10D01E0.01				
	Cross bar construction horizontal						

Alternative to 3a								
3b	Bracket profile attachment lower/back							
Colon.	Material	Colour	Part number					
The same of the sa	Nylon	Dust grey	Z10D01EA.01					
No.	Cross bar construction vertical							

4	SERVO-DRIVE drive unit for drawers						
	Material	Colour	Part number				
Man.	Nylon	Dust grey	Z10A3000.03				
	One SERVO-DRIVE drive unit required per drawer/pull-out						
	Additional accessories dependi	na on installa	tion application				

5	Blum transformer*	
	Blum transformer 24W	Z10NE030D
	Flex	Z10M200K
	Transformer unit housing for cabinet base fixing	Z10NG000
	Alternative: Transformer unit housing for panel fixing	Z10NG120
	Connecting node (1x), Cable end protector (2x)	Z10V100E.01
	SERVO-DRIVE cable 8m** for cutting to size	Z10K800AE
	Cable holder	Z10K0009

<sup>\*</sup>SERVO-DRIVE applications require a transformer for power supply. One transformer can connect up to 50 drawers/pull-outs.

<sup>\*\*</sup>The SERVO-DRIVE cable can be used with a connecting node to extend the power supply cable.


# Additional components required for TIP-ON BLUMOTION applications

TIP-ON BLUMOTION for LEGRABOX

*ablum* 

#### **Product**





2a + 2b	Set containing TIP-ON BLUMOTION unit and TIP-ON BLUMOTION latch									
	Can be used for:			Recommended weight ranges* for an optimum opening and closing function						
39	Nominal length (NL)	Unit	Part number	< 10 kg	20 kg	30 kg	40 kg	50 kg	60 kg	70 kg
	270 mm	S0	T60L7040	≤ 10						
		S1	T60L7140		> 10–20					
	350 – 600 mm	L1**	T60L7340	≤ 2	20					
		L3	T60L7540			15 – 4	ס			
		L5	T60L7570					;	35 – 70	

3	TIP-ON BLUMOTION synchronisation adapter	
	Symmetrical, in combination with synchronisation linkage, two items required per synchronisation linkage, for internal cabinet width ≥ 294 mm	T60.000D
4	TIP-ON BLUMOTION round synchronisation linkage for cutting to size	
	Possible for cabinet widths ≥ 287 mm Suitable for cabinet widths of up to 1400 mm	T60.1125W

Accessories		
	Front gap template for TIP-ON BLUMOTION LEGRABOX / MOVENTO	
	Setting the front gap to 2.5 mm	65.5631

<sup>\*</sup> Total weight of the pull-out


 $<sup>^{\</sup>star\star}$  L1 cannot be used with a 70kg cabinet profile and only to be used with a 40kg cabinet profile.

## Sink Cabinet - height M



#### **Product**





#### **Components required**

1	Cabinet profiles left/right
2	Exterior - drawer side set M height including external and internal cover caps
3	Interior - drawer side set M height including external and internal cover caps
4	Wooden back fixing brackets M height x 4
5	Front fixing bracket x 4

#### Recommended combination of nominal lengths for sink drawer

1,2	Exterior - Drawer side set and cabinet profiles	3	Interior - Drawer side set and cabinet profiles
	Nominal length		Nominal length
	400 mm		270 mm
	450 mm		270 mm
	500 mm		350 mm
	550 mm		400 mm
	600 mm		450 mm


1	Cabinet profiles left/right							
20	Nominal length	BLUMOTION*						
	400 mm	40 kg	750.4001B					
	450 mm	40 kg	750.4501B	70 kg	753.4501B			
	500 mm	40 kg	750.5001B	70 kg	753.5001B			
	550 mm			70 kg	753.5501B			
	600 mm			70 kg	753.6001B			

<sup>\*</sup> Suitable for SERVO-DRIVE

### Sink Cabinet - height M

### **LEGRABOX** pure





4	Wooden back fixing brackets left/right						
Sho		Colour variants					
		SW-M	OG-M	TS-M	Nickel		
		Steel					
لنظل	Height M		ZB7M000S				

5	Front fixing bracket		
	EXPANDO	4 x	ZF7M70E2
	Screw-on	4 x	ZF7M7002


<sup>\*\*</sup> With anti-fingerprint coating

# LEGRABOX pure LEGRABOX free

## Sink Cabinet - height C

#### **Product**





#### **Components required**

1	Cabinet profiles left/right			
2	Exterior - drawer side set C height including external and internal cover caps			
3	Interior - drawer side set M height including external and internal cover caps			
4	Wooden back fixing brackets C height x 2			
5	Wooden back fixing brackets M height x 2			
6	Front fixing bracket x 8			

#### Recommended combination of nominal lengths for sink drawer

1,2	Exterior - Drawer side set and cabinet profiles	3	Interior - Drawer side set and cabinet profiles
	Nominal length		Nominal length
	400 mm		270 mm
	450 mm		270 mm
	500 mm		350 mm
	550 mm		400 mm
	600 mm		450 mm

1	Cabinet profiles left/right							
01) a	Nominal length	BLUMOTION**						
	400 mm	40 kg	750.4001B					
	450 mm	40 kg	750.4501B	70 kg	753.4501B			
	500 mm	40 kg	750.5001B	70 kg	753.5001B			
	550 mm			70 kg	753.5501B			
	600 mm			70 kg	753.6001B			

<sup>\*</sup> Incl. 2 mm tilt adjustment

<sup>\*\*</sup> Suitable for SERVO-DRIVE


# Sink Cabinet - height C

# LEGRABOX pure LEGRABOX free



2	Drawer side set - LEGRABOX pure		
	Consisting of:		
	2a drawer side left/right		
	2b cover caps (external)		
	2c cover caps (internal)		
		Colour variants	
		SW-M OG-M TS-M	INGL
	Nominal length	Steel	Stainless steel**
	400 mm	770C4002S	770C4002I
	450 mm	770C4502S	770C4502I
	500 mm	770C5002S	770C5002I
	550 mm	770C5502S	770C5502I
	600 mm	770C6002S	
2b	Alternative to 2 Drawer side set - LEGRABOX free		
4	Consisting of:		
	2a drawer side left/right		
	2b cover caps (external)		
	2c BOXCOVER front		
	2d BOXCOVER back		
		Colour variants	
		SW-M OG-M TS-M	INGL
	Nominal length	Steel	Stainless steel**
	450 mm	780C4502S	
	500 mm	780C5002S	
	550 mm	780C5502S	780C5502I
01	0 1 1 1 1/11		
2b	Glass design element (side)		
	Nominal length		
	450 mm 1 x		7S338G
	500 mm 1 x		7S388G
7	550 mm 1 x	227	7S438G
3	Drawer side set		
	Consisting of:		
	2a drawer side left/right		
***	2b cover caps (external)		
	2c cover caps (internal)		
		Colour variants	
		SW-M OG-M TS-M	INGL
	Nominal length	Steel	Stainless steel**
	270 mm	770M2702S	
	350 mm	770M3502S	
	400 mm	770M4002S	770M4002I
	450 mm	770M4502S	

# Sink Cabinet - height C





6	Front fixing bracket		
	EXPANDO 6	х	ZF7M70E2
	Screw-on 6	х	ZF7M7002

<sup>\*\*</sup> With anti-fingerprint coating

# **SPACE TOWER**

# **LEGRABOX** pure **LEGRABOX** free

*ablum* 

#### **Product**






#### Recommended configuration

- Shelf
- Inner drawer M height
- Inner pull-out with low glass C height x 2
- Inner pull-out with high glass C height x 2
- Zero protrusion hinge with BLUMOTION or TIP-ON for doors
- Cabinet width 300 mm 600 mm x 1 door
- Cabinet width 600 mm 1200 mm x 2 doors

**Order Specification** 




LEGRABOX pure	SPACE TOWER elements	Order specification and planning information
1	Inner drawer - M height	Refer to page 49
2	Inner pull-out - C height with low glass	Refer to page 55
3	Inner pull-out - C height with low glass	Refer to page 55
4	SPACE TOWER cabinet front - zero protrusion hinge	Refer to page 76

LEGRABOX free	SPACE TOWER elements	Order specification and planning information
1	Inner drawer - M height	Refer to page 49
2	Inner pull-out - C height with low glass	Refer to page 61
3	Inner pull-out - C height with low glass	Refer to page 61
4	SPACE TOWER cabinet front – zero protrusion hinge	Refer to page 76

# **SPACE TOWER**

# **Order Specification**





1	155° zero protrusion hinge	Zinc boss with spring*		Zinc boss unsprung**	
ODS TANK	Overlay application	INSERTA	71T7540N	INSERTA	70T7540NTL
4		Screw-on	71T7500N	Screw-on	70T7500NTL
	Dual application	INSERTA	71T7640N		
	Inset application Use hinges for dual application and	I a 9mm spaced mountir	ng plate.		

2	Mounting Plate				
		Spacing	Height	Part Number	
SEAS	Horizontal cam mounting plate (EXPANDO)	0 mm	8.5 mm	177H3100E	
		3 mm	11.5 mm	177H3130E	
255	Horizontal cam mounting plate	0 mm	8.5 mm	175H3100	
elika	Horizontal cam mounting plate (EXPANDO)	0 mm	8.5 mm	174E6100.01	
		3 mm	11.5 mm	174E6130.01	
8.5	Horizontal cam mounting plate	0 mm	8.5 mm	173H7100	
200		3 mm	11.5 mm	173H7130	

3	BLUMOTION (optional)
	BLUMOTION 973A

<sup>\*</sup> Suitable for BLUMOTION

<sup>\*\*</sup> Suitable for TIP-ON for doors

# **SPACE TOWER**


# LEGRABOX pure LEGRABOX free




4	TIP-ON for doors					
		Colour variants				
		SW	тѕ			
	For drilling	Short version with magnet	965.1004			
1.	For overlay doors up to approx. 1300mm in height. For unsprung hinges Rec. for AVENTOS HK-XS. For drilling Ø10x50mm. Short version, length 50mm incl. 1 x glue-on and 1 x screw-on catch plates.					
	With inline adaptor plate	Short version 20/17	965.1201			
- A	Assembly using chipboard screws Ø3.5mm or Ø4mm or with system screws. For use in combination with TIP-ON short version.					
1	For drilling	Long version with magnet	956A1004			
1/20	For overlay doors starting from approx. 1300mm in height. For unsprung hinges. For drilling Ø10x76mm. Long version, length 76mm incl. 1 x glue-on and 1 x screw-on catch plates.					
	With inline adapter plate	Long version 20/32	956A1004			
	Assembly using chipboard screws Ø3.5mm or Ø4mm or with system screws. For use in combination with TIP-ON long version.					

# **Narrow Cabinet Application**







# **Components required**

1	Cabinet profiles left/right x 1
2a	Drawer side set - M height x 1
2b	Drawer side set - C height x 1
3	Front fixing bracket x 6
4a	Wooden back fixing brackets - M height x 2
4b	Wooden back fixing brackets - C height x 2

# **Order specification**

1	Cabinet profiles left/right					
<i>8</i> 10 ° °	Nominal length	BLUMOTION				
	350 mm	40 kg	750.3501B			
	400 mm	40 kg	750.4001B			
	450 mm	40 kg	750.4501B	70 kg	753.4501B	
	500 mm	40 kg	750.5001B	70 kg	753.5001B	
	550 mm			70 kg	753.5501B	
	600 mm			70 kg	753.6001B	

2	LEGRABOX pure M height					
4.	Consisting of:					
	2a drawer side left/right					
	2b customer branding					
	2c cover caps					
		Colour variants	Colour variants			
		SW-M OG-M TS-M			INGL	
	Nominal length	Steel			Stainless steel**	
	350 mm		770M3502S			
	400 mm		770M4002S		770M4002I	
	450 mm		770M4502S		770M4502I	
	500 mm	770M5002S			770M5002I	
	550 mm	770M5502S		770M5502I		
	600 mm		770M6002S			

# **Narrow Cabinet Application**

# **LEGRABOX** pure **LEGRABOX** free

blum




<sup>\*\*</sup> With anti-fingerprint coating

# **Accessories**

# Ablum


### Side stabiliser

#### **Product**



- Additional stabilisation for extra wide pull-outs
- Recommendation: Cabinet width 900 up to 1400 mm
- Aluminium shaft suitable for KB 1400 mm, for cutting to size
- Suitable for use in combination with BLUMOTION, SERVO-DRIVE and TIP-ON BLUMOTION applications.
- No additional space requirement at the bottom.

#### **Order specification**




# **Accessories**




# **Base stabiliser**

#### **Product**



Base stabiliser	
For stabilising wide drawer bases	Z961.10E1
Reinforces the connection between the base and the front	
Recommendation: from cabinet width of 900 mm, 1 piece	

# **TORX** screwdriver



TORX screwdriver	
Short TORX screwdriver Blade length of 35 mm	SR-DREHTX20 35
Long TORX screwdriver Blade length of 100 mm	SD-DREHTX20 100
TORX size 20 (T20)	
Required for adjusting drawer/pull-out	
Short and long options available to facilitate easy adjustment of drawers and pull- outs of all sizes, narrow or wide.	

# **Assembly devices**

# **Base router**



Base router	
Device that ensures easy and precise rebating of the LEGRABOX pure drawer/pull-out base.	M35.7200
No set up required.	
Suitable for drawer side lengths 270 mm – 600 mm.	
Suitable for 16 mm base thicknesses.	
Components	
1 x Base router machine, 1 x fixing board, 1 x stop bar, 1 x support stop, 1 x cutter DM 44, 1 x depth stop, 1 x timber stop.	

# **MINIPRESS P**



Blum's drilling and fittings insertion specialist facilitating simple construction of cabinets and drawers.	M53.1050
Provides fast, accurate and easy drilling insertion for cabinet profiles, mounting plates, adaptor plates, hinges and drawer fronts.	
Functions pneumatically.	
Thanks to a simple flip chart, adjustments to the machines can be completed quickly and effortlessly.	
For LEGRABOX pure drilling the New MINISTICK is required. This can be easily retro fitted onto existing MINIPRESS P machines.	

# MINISTICK (new)



MINISTICK (new)	
Facilitates easy and precise drilling for LEGRABOX pure when using Blum's MINIPRESS P (required).	MZS.0050
Retro fit option.	
New MINISTICK charts available for usage support.	
Also suitable for TANDEMBOX, runner, hinge and mounting plate drilling.	
Stop system for MINISTICK. *Required for MINIPRESS P purchased prior to 2005.	M30N0200

# **BOXFIX E-L**



BOXFIX E-L	
Provides simple yet precise manual assembly of LEGRABOX drawers and pull-outs.	ZMM.0700
Provides optimal support. The LEGRABOX pure drawer/pull-out parts can be assembled precisely and seamlessly without any awkward holding.	
Easily transported; can be used onsite or in the workshop.	
Can be used to assemble a range of drawer sizes; nominal lengths of 270 mm – 600 mm, cabinet widths from 250 mm – 1200 mm	

# **Assembly devices**



# **Drilling template for LEGRABOX (back and base)**



Drilling template for LEGRABOX	
Template for pre-drilling the fixing holes for LEGRABOX pure drawer/pull-out base width and back.	ZML.700
Ensures exact pre-drilling of the base and back.	
Easily transported; can be used onsite or in the workshop.	
Components	
1 x template, 1 x drilling stop, 1 x allen key	

# **Universal drilling template (drawer front)**



Universal drilling template	
The multifunctional template that combines high precision with practical value.	ZML.0040.01
Facilitates exact marking and pre-drilling positions for front fixing and drawer/pull-out back and base.	
Calibrated for easy adjustment.	
Suitable for LEGRABOX pure, TANDEMBOX drawer systems, MOVENTO, TANDEM and METABOX.	
Components	
1 x Universal drilling template, 1 x drilling depth stop (ø 10 mm), 1 x drilling depth stop (ø 5 mm), 1 x marking template (ø 10 mm), 1 x marking template (ø 5 mm).	

# **Universal drilling template (cabinet profile)**



Universal drilling template	
Facilitates pre-drilling of the fixing positions for cabinet profiles.	65.1000.01
Can be used with assembled and flat pack cabinets.	
Calibrated for setting the height and depth position.	
Suitable for LEGRABOX pure, TANDEMBOX drawer systems, MOVENTO, TANDEM and METABOX.	
Components	
1 x Extension rail 1000 mm, 4 x universal drilling template, 1 x drilling depth spacer Ø 5 mm, 1 x reducing bush Ø 5 to Ø 2.5 mm, 1 x allen key.	

# **AMBIA-LINE**

# **Overview of materials and colour**

*ablum* 

# Steel design










Recommended colour combinations	AMBIA-LINE colours				
	OG-M	TS-M	SW-M		
LEGRABOX colours	Orion Grey Matt	Terra Black Matt	Silk White Matt		
OG-M	_				
Orion Grey Matt	_				
TS-M		_			
Terra Black Matt		_			
SW-M					
Silk White Matt			_		

# **Cutlery insert**







For LEGRABOX applications in Anti-fingerprint Stainless Steel we recommend selecting AMBIA-LINE in Terra Black Matt or Orion Grey Matt.

**Ablum** 

#### **Drawer**





# Order specification for drawer height M and height K

Cutlery insert					
			OG-M TS-M		SW-M/OG-M
	Nominal length	Width			
	450 mm	300 mm	zc	C7S450BS3	
	500 mm	300 mm	zo	C7S500BS3	
	550 mm	300 mm	zc	C7S550BS3	
	600 mm	300 mm	zo	C7S600BS3	
	Adapter profile not required	for cutlery insert			

Drawer frame for nominal lengths of 270 mm or more						
			OG-M	TS-M	SW-M	
	Nominal length	Width				
	from 270 mm	242 mm		ZC7S300RSU		
	With magnet for connection to the adapter profile or drawer side					

Adapter profile for connection to chipboard back						
			OG-M	TS-M	SW-M	
	Height	Width				
	М	242 mm	ZC7A0U0M			
	K	242 mm		ZC7A0U0K		
	Not required for NL 270  Recommended for NL greater than 350 mm  Required for all LEGRABOX free and LEGRABOX pure in Anti-fingerprint Stainless Steel applications.					

Individual cross divider (optional)						
			OG-M	TS-M	SW-M	
	Height	for width				
	50 mm	242 mm		ZC7Q0U0SS		

# **AMBIA-LINE**

# Steel design

# *ablum*

#### **Drawer**





Drawer fran	Drawer frame – narrow					
			OG-M	TS-M	SW-M	
	Nominal length	Width				
	450 mm	100 mm		ZC7S450RS1		
	500 mm	100 mm		ZC7S500RS1		
	550 mm	100 mm		ZC7S550RS1		
	600 mm	100 mm		ZC7S600RS1		

Individual cross divider (optional)						
			OG-M	TS-M	SW-M	
	Height	for width				
	50 mm	100 mm		ZC7Q010SS		

Dra	Drawer frame – wide						
				OG-M	TS-M	SW-M	
		Nominal length	Width				
		450 mm	200 mm		ZC7S450RS2		
1		500 mm	200 mm		ZC7S500RS2		
		550 mm	200 mm		ZC7S550RS2		
		600 mm	200 mm		ZC7S600RS2		
	<b>/</b> /						

Individual cross divider (optional)						
			OG-M	TS-M	SW-M	
	Height	for width				
7	50 mm	200 mm		ZC7Q020SS		


For planning, assembly, installation and adjustment information please refer to Blum's trade catalogue, DYNALOG planning and ordering software, Blum Product Configurator and/or our EASY ASSEMBLY App.

*ablum* 

### **High fronted pull-out**



# Order specification for high fronted pull-out height C and height F



Adapter pro	Adapter profile for connection to chipboard back							
			OG-M	TS-M	SW-M			
	Height	Width						
7	С	242 mm		ZC7A0U0C				
	Not required for N	NL 270 and 300 mm						
	Recommended for NL greater than 350 mm							
	Required for all L	EGRABOX free and LEGRABOX pure in An	ti-fingerprint Stainless Steel	applications.				

Individual cross divider (optional)						
			OG-M	TS-M	SW-M	
	Height	for width				
7	110 mm	242 mm		ZC7Q0U0FS		
	110 mm	218 mm		ZC7Q0P0FS		

High fronted pull-out frame for nominal lengths of 400 mm or more							
			OG-M	TS-M	SW-M		
	Nominal length	Width					
$\checkmark$	from 400 mm	218 mm		ZC7F400RSP			
	With magnet for connection to the adapter profile or drawer side						

# **AMBIA-LINE**

# Steel design





**Ablum** 

### **High fronted pull-out**





# Order specification for high fronted pull-out height C and height F

Cross galle	ery for cutting to size		
3.000 3	,, (a) catalog co cazo	OG-M TS-M	SW-M
	tength 1080 mm	ZR7.1080U	
	Cutting: LW-90 mm		
Connector	s		
_		OG-M TS-M	SW-M
	LEGRABOX pure	ZC7U10E0	
	LEGRABOX free	ZC7U11E0	
Lateral divi	der		
		OG-M TS-M	SW-M
, ON	Length 84 mm	ZC7U10F0	

# Steel design



### **AMBIA-LINE** bottle set



### **Order specification**

	Nominal length	Width	OG-M	TS-M	SW-M
	from 450 mm	100 mm	ZC7B0100S		
Dr.	from 450 mm	200 mm		ZC7B0200S	
Not suitable f	or inner pull-outs				

Drawer fram	Drawer frame – narrow						
	Nominal length	Width	OG-M	TS-M	SW-M		
	450 mm	100 mm		ZC7S450RS	1		
	500 mm	100 mm		ZC7S500RS	1		
	550 mm	100 mm		ZC7S550RS	1		
	600 mm	100 mm		ZC7S600RS	1		

Drawer fram	Drawer frame – wide						
	Nominal length	Width	OG-M	OG-M TS-M SW-M			
	450 mm	200 mm		ZC7S450RS2			
	500 mm	200 mm		ZC7S500R	IS2		
	550 mm	200 mm		ZC7S550R	IS2		
	600 mm	200 mm		ZC7S600RS2			

For planning, assembly, installation and adjustment information please refer to Blum's trade catalogue, DYNALOG planning and ordering software, Blum Product Configurator and/or our EASY ASSEMBLY App.

# Kitchen accessories

**AMBIA-LINE** 





# **Order specification**

Knife holder						
	Length	Width				
	409 mm	186 mm				
	For 9 knives		OG-M	ZC7M0200		
	For drawer height M and height K					
	Nominal length from 450 mm and greater					

Foil/film dispenser					
	Length	Width			
	409 mm	187 mm			
	Double unit, cling film and aluminium foil, without film/foil		OG-M	ZC7C0001	
	Compatible with foil / cling film with dimensions: Diameter 46 mm and length 330 mm.				
	For drawer height M and height K				
	Nominal length from 450 mm and greater				

Spice holder					
	Length	Width			
	356 mm	200 mm	OG-M	ZC7G0P0I	
	For high fronted pull-out height C and height F				
	Suitable for use with ZC7F400RSP				

Blum Plate holder					
G	Plate diameter	Stacking height			
	186–322 mm	up to 12 plates (146 mm)	OG-M	ZC7T0350	
	Overall Plate Holder height: 170 mm				
	For high fronted pull-out height C and height F				



Founded over 60 years ago by Julius Blum, today Blum is an internationally active family-owned company. Blum is trusted and renowned worldwide for designing a comprehensive range of high quality industry leading products that significantly enhance user convenience and ergonomics in the kitchen and throughout the home. That's why we make every effort to perfect the motion of our lift, hinge, box and runner systems.





#### Design is more than an attractive appearance

Form, function and the focus on perfecting motion are and have always been firmly interlinked at Blum. This means that Blum products turn the use of high-quality furniture into a true experience and offer the ideal fitting solution for every home. Blum incorporates current design trends, personal preferences and functional furniture use. Blum fittings are internationally recognised for their sophisticated design and functional excellence.

#### Quality for the lifetime of the furniture

For over 60 years, quality has been the highest principle for the development and manufacture of Blum products. Our fittings exemplify quality with their well-thought-out function and durability, engineered to provide problem free use for the lifetime of the furniture. We achieve this by using the strictest internal guidelines and rigorous testing that form the basis of our ISO9001 Quality Management System.







#### Innovation for high living comfort

We want our fitting solutions to be innovative and make everyday kitchen use easier. That's why our developments are based on findings from requirements research and input from our customers. Blum is one of the largest patent applicants in Austria and has more than 1,000 registered trademarks. CLIP, tool free assembly, TANDEM technology, MOVENTO technology, LEGRABOX Box system, BLUMOTION soft close, SERVO-DRIVE electrical motion support system and TIP-ON BLUMOTION mechanical motion support system are all innovations by Blum and milestones in the furniture manufacturing industry.

#### Our contribution to the environment

Blum strives to minimise its environmental impact with environmental protection being an integral part of everything we do. We use environmentally friendly processes, use raw materials intelligently and save energy wherever we can. Our commitment to environmental protection is internationally recognised and rewarded. We endeavour to maintain and are always looking to improve our environmental management systems.











Blum Showrooms Sydney (Head Office)

10 Blackbird Close Len Waters Estate NSW 2170 Ph: 02 9612 5400

#### **Adelaide**

179 Railway Terrace Mile End SA 5031 Ph: 08 8118 6070

#### **Brisbane**

6/39-45 Compton Road Underwood QLD 4119 Ph: 07 3135 9490

#### Melbourne

245 Ferntree Gully Road Mount Waverley VIC 3149 Ph: 03 9982 1720

#### Perth

3/50 Howe Street Osborne Park WA 6916 Ph: 08 6467 0110

Place distributor or company contact details here.

Blum Australia Pty. Ltd. P.O. Box 1615 Green Valley NSW 2168 Toll Free: 1800 179 186 E-Mail: info.au@blum.com

